

Dimension(mm) & Image		<p>Super slim</p>	<p>Super slim</p>		
Model	MO-T100L-3S	MO-T100U-3M	MO-T100D-3M	MO-T100U-3X MO-T100LU-3X6(LED)	MO-T100D-3X MO-T100LD-3X6(LED)
Camera type	front view	up view	down view	up view	down view
Built-in Lens	3.4mm/F7.0 (with LED) 3.4mm/F3.4 (no LED)	3.4mm/F2.8 (no LED)	3.4mm/F2.8 (no LED)	3.4mm/F2.8 (no LED) 3.4mm/F6.0 (with LED)	3.4mm/F2.8 (no LED) 3.4mm/F6.0 (with LED)
LED light illumination	white LED x 8 (specify when ordering)	N/A (specify when ordering)	N/A (specify when ordering)	N/A (specify when ordering)	N/A (specify when ordering)
Video system	NTSC / PAL				
Number of effective pixels	648 x 480				
Image sensor	1/4" CCIQ II Color Camera				
Resolution(TV Lines)	400 TV Lines				
S/N Ratio	more than 50dB				
Minimum illumination	0.1 LUX / F1.2				
Image Transfer Rate	60 field/sec (NTSC), 50 field/sec (PAL)				
Horizontal sync frequency	NTSC(EIA) -15.734kHz, PAL(CCIR) - 15.625kHz				
Vertical sync frequency	NTSC(EIA) - 60Hz, PAL(CCIR) - 50Hz				
Camera consumption	0.45				
Video output	1Vp-p, 75ohm composite				
Storage temperature	-30 to 60 Degree C				
Working temperature	-10 to 45 Degree C				
Power source	Camera :DC 5V				
Power current	270mA-max				